

Applicants: SMOLYAR, Lev, et al.  
Serial No.: 09/966,753  
Filed: October 1, 2001  
Page 3

RECEIVED  
CENTRAL FAX CENTER

JAN 17 2007

### AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listing of claims in the Application. Please amend the claims to read as follows:

1. **(Previously Presented)** A rake receiver comprising:  
  
a direction metric determiner which generates direction metrics of each of a set of possible directions of joint movement of at least two fingers of a finger block of the rake receiver;  
  
a metric selector which selects one of said direction metrics according to a predetermined criterion; and  
  
a finger adjuster which moves the fingers of said finger block in the directions indicated by said selected direction metric.
2. **(Original)** A receiver according to claim 1, wherein said selected direction metric is the maximal direction metric.
3. **(Original)** A receiver according to claim 1, wherein said finger adjuster moves the fingers of said finger block only if said selected direction metric is the maximal direction metric and exceeds a comparison direction metric by at least a predetermined threshold.
4. **(Original)** A receiver according to claim 1, wherein said finger adjuster includes a redefiner which redefines finger blocks once said fingers have been moved.
5. **(Original)** A receiver according to claim 1, wherein said finger block is formed of two fingers.

Applicants: SMOLYAR, Lev, et al.  
Serial No.: 09/966,753  
Filed: October 1, 2001  
Page 4

6. (Original) A receiver according to claim 5, wherein said determiner generates said direction metrics for five different directions of joint movement.
7. (Original) A receiver according to claim 5, wherein said determiner generates said direction metrics for six different directions of joint movement.
8. (Original) A receiver according to claim 5, wherein said determiner generates said direction metrics for nine different directions of joint movement.
9. (Original) A receiver according to claim 1, wherein said finger block is formed of two closely spaced fingers.
10. (Original) A receiver according to claim 9, wherein said closely spaced fingers are  $7/8$  chip apart.
11. (Original) A receiver according to claim 1, wherein said finger block is formed of three fingers.
12. (Original) A receiver according to claim 1, wherein delays between fingers are set to be no smaller than  $7/8$  chip.
13. (Original) A receiver according to claim 1, wherein said direction metrics are based on power estimation.
14. (Currently Amended) An article comprising a computer readable storage medium having [[stored]] encoded thereon instructions, that, when executed by a computing platform, cause the computing platform to generate direction metrics of each of a set of possible directions of joint movement of at least two fingers of a finger block of a rake receiver, select one of said direction metrics according to a predetermined

Applicants: SMOLYAR, Lev, et al.  
Serial No.: 09/966,753  
Filed: October 1, 2001  
Page 5

criterion, and to move the fingers of said finger block in the directions indicated by said selected direction metric.

15. (Original) The article according to claim 14, wherein said selected direction metric is the maximal direction metric.
16. (Currently Amended) The article according to claim 15, wherein the fingers of said finger block [[is]] are adjusted only if said selected direction metric is the maximal direction metric and exceeds a comparison direction metric by at least a predetermined threshold.
17. (Original) The article according to claim 14, further having stored instructions which cause the computing platform to redefine the finger blocks.
18. (Original) The article according to claim 14, wherein said finger block is formed of two fingers.
19. (Original) The article according to claim 18, wherein said direction metrics are generated for five different directions of joint movement.
20. (Original) The article according to claim 18, wherein said direction metrics are generated for six different directions of joint movement.
21. (Original) The article according to claim 18, wherein said direction metrics are generated for nine different directions of joint movement.
22. (Original) The article according to claim 14, wherein said finger block is formed of two closely spaced fingers.

Applicants: SMOLYAR, Lev, et al.  
Serial No.: 09/966,753  
Filed: October 1, 2001  
Page 6

23. (Original) The article according to claim 22, wherein said closely spaced fingers are  $7/8$  chip apart.
24. (Original) The article according to claim 14, wherein said finger block is formed of three fingers.
25. (Original) The article according to claim 14, wherein delays between fingers are set to be no smaller than  $7/8$  chip.
26. (Currently Amended) The article according to claim 14, wherein said ~~step of~~ generating of direction metrics includes the step of time averaging said direction metrics by summing consecutive direction metrics.
27. (Original) The article according to claim 26, wherein said step of time averaging uses a forgetting factor.
28. (Original) The article according to claim 14, wherein said direction metrics are based on power estimation.
29. (Cancelled)
30. (Previously Presented) A method comprising:
  - forming a finger block of at least two fingers of a rake receiver; and
  - jointly tracking the fingers of said finger block by:
    - generating direction metrics of each of a set of possible directions of joint movement of the fingers of said finger block;
    - selecting one of said direction metrics according to a predetermined criterion; and
    - moving the fingers of said finger block in the directions indicated by said selected direction metric.